






Thermal Transmittance (U-Value) Data Metric Standard Units




Reference #:	O136-15	
Client/Site:	COMEP INFISSI SRL / USA CERTIFICATION	
Spacer Type	PVC Spacer	
Uw (Average)	1.73 W/(m*K)	
	Item:	1
	Type:	1
	Description:	SINGLE CASEMENT WINDOW (OUT-SWING)
	Quantity:	1
	Size (MM):	600.0 x 1500.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Double Glaze PVC spacer
Uw (U-value)	1.9 W/(m*K)	
	Item:	2
	Type:	2
	Description:	SINGLE CASEMENT WINDOW (IN-SWING)
	Quantity:	1
	Size (MM):	600.0 x 1500.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Double Glaze PVC spacer
Uw (U-value)	1.8 W/(m*K)	
	Item:	3
	Type:	3
	Description:	FIXED UNIT
	Quantity:	1
	Size (MM):	1200.0 x 1500.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Double Glaze PVC spacer
Uw (U-value)	1.5 W/(m*K)	
	Item:	4
	Type:	4
	Description:	SINGLE CASEMENT DOOR (IN-SWING)
	Quantity:	1
	Size (MM):	1000.0 x 2000.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Double Glaze PVC spacer
Uw (U-value)	1.5 W/(m*K)	
	Item:	5
	Type:	5
	Description:	SINGLE CASEMENT WINDOW (OUT-SWING)
	Quantity:	1
	Size (MM):	1000.0 x 2000.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Double Glaze PVC spacer
Uw (U-value)	1.6 W/(m*K)	
	Item:	6
	Type:	6
	Description:	SINGLE TILT AND TURN WINDOW (IN-SWING)
	Quantity:	1
	Size (MM):	600.0 x 1500.0
	Profile series:	EBE-65
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Double Glaze PVC spacer
Uw (U-value)	1.9 W/(m*K)	


	Item:	7
	Type:	7
	Description:	LIFT AND SLIDE DOOR
	Quantity:	1
	Size (MM):	2000.0 x 2000.0
	Profile series:	EBE-65
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Double Glaze PVC spacer
	Uw (U-value)	1.9 W/(m*K)


	Item:	8
	Type:	8
	Description:	SINGLE CASEMENT DOOR (IN-SWING)
	Quantity:	1
	Size (MM):	1000.0 x 2000.0
	Profile series:	EBE-65
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Double Glaze PVC spacer
	Uw (U-value)	1.7 W/(m*K)


	Item:	9
	Type:	9
	Description:	SINGLE CASEMENT DOOR (OUT-SWING)
	Quantity:	1
	Size (MM):	1000.0 x 2000.0
	Profile series:	EBE-65
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Double Glaze PVC spacer
	Uw (U-value)	1.7 W/(m*K)


Reference #:	O136-15
Client/Site:	COMEP INFISSI SRL / USA CERTIFICATION
Spacer Type:	Std Spacer
Uw (Average)	1.82 W/(m*K)


	Item:	1
	Type:	1
	Description:	SINGLE CASEMENT WINDOW (OUT-SWING)
	Quantity:	1
	Size (MM):	600.0 x 1500.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Double glaze Std spacer
	Uw (U-value)	2.0 W/(m*K)


	Item:	2
	Type:	2
	Description:	SINGLE CASEMENT WINDOW (IN-SWING)
	Quantity:	1
	Size (MM):	600.0 x 1500.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Double glaze Std spacer
	Uw (U-value)	1.8 W/(m*K)


	Item:	3
	Type:	3
	Description:	FIXED UNIT
	Quantity:	1
	Size (MM):	1200.0 x 1500.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Double glaze Std spacer
	Uw (U-value)	1.6 W/(m*K)


	Item:	4
	Type:	4
	Description:	SINGLE CASEMENT DOOR (IN-SWING)
	Quantity:	1
	Size (MM):	1000.0 x 2000.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Double glaze Std spacer
	Uw (U-value)	1.6 W/(m*K)

	Item:	5
	Type:	5
	Description:	SINGLE CASEMENT DOOR (OUT-SWING)
	Quantity:	1
	Size (MM):	1000.0 x 2000.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Double glaze Std spacer
	Uw (U-value)	1.7 W/(m*K)


	Item:	6
	Type:	6
	Description:	SINGLE TILT AND TURN WINDOW (IN-SWING)
	Quantity:	1
	Size (MM):	600.0 x 1500.0
	Profile series:	EBE-65
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Double glaze Std spacer
	Uw (U-value)	2.1 W/(m*K)


	Item:	7
	Type:	7
	Description:	LIFT AND SLIDE
	Quantity:	1
	Size (MM):	2000.0 x 2000.0
	Profile series:	EBE-65
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Double glaze Std spacer
	Uw (U-value)	2.0 W/(m*K)


	Item:	8
	Type:	8
	Description:	SINGLE CASEMENT DOOR (IN-SWING)
	Quantity:	1
	Size (MM):	1000.0 x 2000.0
	Profile series:	EBE-65
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Double glaze Std spacer
	Uw (U-value)	1.8 W/(m*K)


	Item:	9
	Type:	9
	Description:	SINGLE CASEMENT DOOR (OUT-SWING)
	Quantity:	1
	Size (MM):	1000.0 x 2000.0
	Profile series:	EBE-65
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Double glaze Std spacer
	Uw (U-value)	1.8 W/(m*K)


Reference #:	O136-15
Client/Site:	COMEP INFISSI SRL /USA CERTIFICATION
Spacer Type:	PVC Spacer
Uw (Average)	1.48W/(m*K)


	Item:	1
	Type:	1
	Description:	SINGLE CASEMENT WINDOW (OUT-SWING)
	Quantity:	1
	Size (MM):	600.0 x 1500.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Triple glaze PVC spacer
	Uw (U-value)	1.6 W/(m*K)


	Item:	2
	Type:	2
	Description:	SINGLE CASEMENT WINDOW (IN-SWING)
	Quantity:	1
	Size (MM):	600.0 x 1500.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Triple glaze PVC spacer
	Uw (U-value)	1.6 W/(m*K)


	Item:	3
	Type:	3
	Description:	FIXED UNIT
	Quantity:	1
	Size (MM):	1200.0 x 1500.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Triple glaze PVC spacer
	Uw (U-value)	1.2 W/(m*K)


	Item:	4
	Type:	4
	Description:	SINGLE CASEMENT DOOR (IN-SWING)
	Quantity:	1
	Size (MM):	1000.0 x 2000.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Triple glaze PVC spacer
	Uw (U-value)	1.3 W/(m*K)

	Item:	5
	Type:	5
	Description:	SINGLE CASEMENT DOOR (OUT-SWING)
	Quantity:	1
	Size (MM):	1000.0 x 2000.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Triple glaze PVC spacer
	Uw (U-value)	1.3 W/(m*K)


	Item:	6
	Type:	6
	Description:	SINGLE TILT AND TURN WINDOW (IN-SWING)
	Quantity:	1
	Size (MM):	600.0 x 1500.0
	Profile series:	EBE-65
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Triple glaze PVC spacer
	Uw (U-value)	1.8 W/(m*K)


	Item:	7
	Type:	7
	Description:	LIFT AND SLIDE
	Quantity:	1
	Size (MM):	2000.0 x 2000.0
	Profile series:	EBE-65
	Color:	N/A
	Materials:	Galvanized Steel
	Glazing:	Triple glaze PVC spacer
	Uw (U-value)	1.7 W/(m*K)


	Item:	8
	Type:	8
	Description:	SINGLE CASEMENT DOOR (IN-SWING)
	Quantity:	1
	Size (MM):	1000.0 x 2000.0
	Profile series:	EBE-65
	Color:	N/A
	Materials:	Galvanized Steel
	Glazing:	Triple glaze PVC spacer
	Uw (U-value)	1.5 W/(m*K)


	Item:	9
	Type:	9
	Description:	SINGLE CASEMENT DOOR (OUT-SWING)
	Quantity:	1
	Size (MM):	1000.0 x 2000.0
	Profile series:	EBE-65
	Color:	N/A
	Materials:	Galvanized Steel
	Glazing:	Triple glaze PVC spacer
	Uw (U-value)	1.5 W/(m*K)


Reference #:	O136-15
Client/Site:	COMEP INFISSI SRL /USA CERTIFICATION
Spacer Type:	PVC SPACER
Uw (Average)	1.57 W/(m*K)


	Item:	1
	Type:	1
	Description:	SINGLE CASEMENT WINDOW (OUT-SWING)
	Quantity:	1
	Size (MM):	600.0 x 1500.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Triple glaze PVC spacer
	Uw (U-value)	1.8 W/(m*K)


	Item:	2
	Type:	2
	Description:	SINGLE CASEMENT WINDOW (IN-SWING)
	Quantity:	1
	Size (MM):	600.0 x 1500.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Triple glaze PVC spacer
	Uw (U-value)	1.7 W/(m*K)


	Item:	3
	Type:	3
	Description:	FIXED UNIT
	Quantity:	1
	Size (MM):	1200.0 x 1500.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Triple glaze PVC spacer
	Uw (U-value)	1.3 W/(m*K)


	Item:	4
	Type:	4
	Description:	SINGLE CASEMENT DOOR (IN-SWING)
	Quantity:	1
	Size (MM):	1000.0 x 2000.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Triple glaze PVC spacer
	Uw (U-value)	1.4 W/(m*K)

	Item:	5
	Type:	5
	Description:	SINGLE CASEMENT DOOR (OUT-SWING)
	Quantity:	1
	Size (MM):	1000.0 x 2000.0
	Profile series:	OS2
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Triple glaze PVC spacer
	Uw (U-value)	1.4 W/(m*K)

	Item:	6
	Type:	6
	Description:	SINGLE TILT AND TURN WINDOW (IN-SWING)
	Quantity:	1
	Size (MM):	600.0 x 1500.0
	Profile series:	EBE-65
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Triple glaze PVC spacer
	Uw (U-value)	1.9 W/(m*K)

	Item:	7
	Type:	7
	Description:	LIFT AND SLIDE
	Quantity:	1
	Size (MM):	2000.0 x 2000.0
	Profile series:	EBE-65
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Triple glaze PVC spacer
	Uw (U-value)	1.7 W/(m*K)

	Item:	8
	Type:	8
	Description:	SINGLE CASEMENT DOOR (IN-SWING)
	Quantity:	1
	Size (MM):	1000.0 x 2000.0
	Profile series:	EBE-65
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Triple glaze PVC spacer
	Uw (U-value)	1.6 W/(m*K)

	Item:	9
	Type:	9
	Description:	SINGLE CASEMENT DOOR (OUT-SWING)
	Quantity:	1
	Size (MM):	1000.0 x 2000.0
	Profile series:	EBE-65
	Color:	N/A
	Material:	Galvanized Steel
	Glazing:	Triple glaze PVC spacer
	Uw (U-value)	1.6 W/(m*K)